

Sliding guide rail closers



CT4500

EN 1154 CERTIFIED
Fire door 

Door closer with Cam-Motion® technology and height-adjustable guide rail GD300F or standard guide rail GD3000

- » Fulfills barrier-free building requirements (DDA / CEN TR 15894)
- » Certified in compliance with EN 1154, size 1-4
- » Suitable for fire and smoke protection doors
- » Can be used in four installation types: hinge and non-hinge sides in standard and frame installation
- » Axis continuously height adjustable up to 14 mm
- » Closing speed, latching speed and backcheck adjustable via front facing regulating valves
- » Internal safety valve with pressure relief action.


EN 1154:1996 + A1:2002 certified: **3 8 1/4 1 1 3**



*When mounted at the PUSH side.

The CAM MOTION drive:

CT4500 works with the exclusive symmetric CAM MOTION drive that the brilliant CT5000 has made famous. By achieving the highest efficiency and torque output characteristics, the CT4500 makes the door opening feel smooth as silk while assuring a reliable door closing under all circumstances. Approved for use in DEC environment like Elderly homes, health care facilities and kindergartens. (DEC= Disabled, Elderly and Children)



Size (EN 1154)	Door width cm	Door weight Kg
1	75	20
2	85	40
3	95	60
4	110	80

Model	Size	Finish
CT450014BL	1 - 4	White
CT450014NE	1 - 4	Black
CT450014PL	1 - 4	Silver
CT450014IM	1-4	Stainless steel