ABLOY® CYL403





Used with rim and mortice lock cases. Length: 1¼ inch. Case hardened steel.

- Overview of Advantages
 Strong burglary protection
 Suitable for both outer and inner door use
- Adjustable during installation to match different door thicknesses
 Several plating options



28,64 THD. 1.150-32 UNS 2A ØTHD. 12-24 UNC 2B

Technical data

Available key systems	ABLOY PROTEC CLIQ ABLOY PROTEC ² CLIQ
Available plating options	Brushed chrome (CrHa), Brushed nickel (NiHa), Bright brass (MSKiLa)
Cylinder ring diameter	46mm
Suitable for fire doors	Yes
ANSI Standard	UL-437 LISTED
Weight	0,22 kg

- Cylinder memory
 1800 authorized key groups and programming keys together, theoretical maximum 65535 keys in each group
 A list of 3000 denied keys
 Audit trail of last 2000 events
 Audit trail of last 20 events from keys in other

- systems

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

