ABLOY® PLL330





All-purpose padlock, key can be removed only in locked position.

Overview of Advantages

- Durable construction even in harsh environment Corrosion resistant
- · Suitable for storage doors, gates, power stations switches, trailers, motorcycles, etc.



54

48

Technical data

Available key systems	ABLOY PROTEC CLIQ, ABLOY PROTEC ² CLIQ
Body	Made of brass, bright chrome (Cr) plated
Body size	48 x 22 x 43 mm (width x thickness x height)
Shackle	Diameter 8 mm, heights 25 mm, 50 mm and 100 mm, material case hardened boron steel, stainless steel or brass. (Boron steel and brass chromium plated).
Security grading: EN 12320:2012 SENTRY (B), SENTO (Z), PRTOEC2 (T)	Grade 3 (25/50 mm shacle only), SSFN014 Grade 2 (25/50 mm shacle only)
Weight	0,39 kg

Cylinder memory

- 1800 authorized key groups and programming keys together, theoretical maximum 65535 keys in each group A list of 3000 denied keys

- Audit trail of last 2000 events
 Audit trail of last 20 events from keys in other systems

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

