

## Door fittings suitable for emergency exit devices pursuant to EN 179 No. 190829\_01

- |   |   |
|---|---|
| <b>1. ID code of the product type:</b>  | Door lever handle   |
| <b>2. Type number:</b>  | EH004 (FORUM 4 EXIT), EH006 (POLAR 6 EXIT),<br>EH060 (PRESTO 3-20 EXIT), EH070 (INOXI 3-19<br>EXIT), EH073 (INOXI 3-19k EXIT)<br><br>Approved plate types:<br>042, 040, 0750, 0730<br>/242<br>/2750 |
| <b>3. Intended use:</b>   | For doors on escape routes  |
| <b>4. Manufacturer:</b>   | Abloy Oy<br>Joensuu factory<br>Wahlforssinkatu 20<br>FI-80100 JOENSUU<br>FINLAND  |
| <b>5. System or systems of assessment and verification of constancy of performance of the construction product:</b> | AVCP 1  |
| <b>6. Notified product certification body:</b>  | MPA NRW<br>Materialprüfungsamt Nordrhein-Westfalen<br>ID No: 0432<br>Marsbruchstraße 186<br>44287 Dortmund-Aplerbeck<br>GERMANY   |
| <b>CE Certificate and DO number:</b>  | No 0432-CPR-00008-01<br>DO 20.33.01, DO 20.33.02  |

## 7. Declared performance:

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	<b>3</b>	High frequency of use where there is little intensive to exercise care	<b>EN 179:2008</b>
7.2 Durability	<b>7</b>	200 00 test cycles	
7.3 Door mass	<b>6</b>	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	<b>B</b>	Approved for use on fire/smoke door assemblies	
7.5 Safety	<b>1</b>	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	<b>3</b>	96 h (high resistance)	
7.7 Security	<b>4</b>	3 000 N	
7.8 Projection of operating element	<b>2</b>	Projection up to 100 mm (standard projection)	
7.9 Type of operation	<b>A</b>	Emergency exit device with "lever handle" operation	
7.10 Field of door application	<b>A / B</b>	Outwardly opening single exit door, double exit door: active or inactive leaf only / outwardly opening single exit door only.	
<b>Dangerous substances</b>	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2019-08-29  
On behalf of Abloy Oy



Jari Kervinen  
CTO