

Declaration of performance No. 21020-1

- 1. ID code of the product type:** Electric Lock
- 2. Type number:** EL460L, EL560L, EL564L
- 3. Intended use:** For doors on escape routes
- 4. Manufacturer:** Abloy Oy
Joensuu factory
Wahlforssinkatu 20
FI-80100 JOENSUU
FINLAND
- 5. System or systems of assessment and verification of constancy of performance of the construction product:** AVCP 1
- 6. Notified product certification body:** MPA NRW
Materialprüfungsamt Nordrhein-Westfalen
ID No: 0432
Marsbruchstraße 186
44287 Dortmund
GERMANY
- CE Certificates:** No. 0432-CPR-00008-2, version 05
No. 0432-CPR-00008-1, version 05

7. Declared performance:

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	3	High frequency of use where there is little intensive to exercise care	EN 1125:2008
7.2 Durability	7	200 000 test cycles	
7.3 Door mass	6	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	B	Suitable for use on fire door assemblies based on a test in accordance with EN 1634-1	
7.5 Safety	1	All panic exit devices have a critical safety function	
7.6 Corrosion resistance	3	96 h (high resistance)	
7.7 Security	2	1000 N	
7.8 Projection of horizontal bar	1	Projection up to 150 mm (large projection)	
7.9 Type of horizontal bar operation	A	Panic exit device with "push-bar" operation	
7.10 Field door application	B	Single door only	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

Essential Characteristics	Grade	Performance	Harmonized technical specification
7.1 Category of use	3	High frequency of use where there is little intensive to exercise care	EN 179:2008
7.2 Durability	7	200 000 test cycles	
7.3 Door mass	6	Up to 200 kg	
7.4 Suitability for use on fire/smoke doors	0 / B *)	Not suitable for use on fire door assemblies / Suitable for use on fire door assemblies based on a test in accordance with EN 1634-1	
7.5 Safety	1	All emergency exit devices have a critical safety function	
7.6 Corrosion resistance	3	96 h (high resistance)	
7.7 Security	4	3 000 N	
7.8 Projection of operating element	2	Projection up to 100 mm (standard projection)	
7.9 Type of operation	A	Emergency exit device with "lever handle" operation	
7.10 Field of door application	B	Outwardly opening single exit door only	
Dangerous substances	The materials used in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.		

*) Note, more details in installation instructions

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance point 7. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Joensuu 2022-07-21
On behalf of Abloy Oy



Jari Keränen, VP Mechanical Solutions

Joensuu 2021-07-21
On behalf of Abloy Oy



Minna Sallinen, VP Digital Access Solutions