

ABLOY[®] CYL321 Electromechanical CLIQ DIN/Europrofile Single Cylinder

Product description Electromechanical CLIQ Single cylinder to be used with mortice lock cases and other applications with DIN / Europrofile cylinder dimensions.

Lock is operated with an electronic CLIQ key from outside.

- $\ensuremath{\textbf{Overview of Advantages}}\xspace$ \cdot Can be use with wide range applications for DIN cylinders
- Strong burglary protection
- Suitable for both outer and inner door use
 Adjustable length with extension system to match different door thicknesses
 Adjustable locked position of cam
- · Several plating options





Technical data

ABLOY PROTEC ² CLIQ
Brass
Bright chrome (Cr), Satin chrome (HCr), Brushed nickel (NiHa), Bright brass (MSKiLa), Satin brass (MSHaLa)
38 mm
with 5 mm steps 32–82 mm, and with 10 mm steps 88–132 mm
Yes
Key related security 6, attack resistance D
0.17 kg

Cylinder memory

- 1800 authorized key groups and programming keys together, theoretical maximum 65535 A list of 3000 denied keys
 Audit trail of last 2000 events
 Audit trail of last 20 events from keys in other systems

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."

