

High range latch

134U Plus Series

Features

- » Mortise lock for wooden doors.
- » Distance between shafts: 70 mm.
- » Backset: 50.
- » Valid for both passage and deadbolt doors.
- » Automatic unblocking of deadbolt: if the deadbolt is activated with an open door, this will be released when it is closed.
- » Reversible latch made of AISI 304 wrought stainless steel. Silent, fire-resistant.
- » Handle follower rod: 8mm. Deadbolt follower rod: 6 mm.
- » 23 mm front, square or round-shaped.
- » Housings conform to DN standard for double rapiers.
- » Packaging in one single box.
- » Certified according to the 12209 CE-EN standard.
- » With strike protector.

Finishes

- » Brass steel (HL)
- » Nickel brass (HN)
- » Glazed steel (AE)
- » AISI 430 stainless steel (AI)
- » Antique brass (LA)

Classification

3	S	8	1	F	0	NA	B	0	2	0
Category of use	Durability and load on latch bolt	Door mass and closing force.	Suitability for use on fire/smoke doors.	Safety	Corrosion resistance and temperature.	Security and drill resistance.	Fields of application for doors.	Type of key manoeuvre and blocking.	Type of manoeuvre in the follower rod	Requirements for key identification.

Model	Backset. 1/2 round forend or square	Finish	Packaging
134UP	5R / 50	AE	1
134UP	5R / 50	HN	1
134UP	5R / 50	HL	1
134UP	5R / 50	AI	1

