

Multipoint security

Security

A

TLB Series

- » Circular roller bolts in the main lock. (Ø14mm. diameter).
- » Plane edge roller bolts in auxiliary locks.
- » Mechanisms protected in galvanised steel closed cases.
- » Floor & Top Jamb locking bolts in hardened steel (TLB5).
- » Steel made Floor & Top Jamb strikes. Floor strike includes dust proof lid.
- » "U" profile steel faceplate provides great strength and is ideal for Fire Doors.
- » Auxiliary locks mechanisms provided with anti-return system.
- » Full size strikeplates are 40mm. width. Optional 35mm and 45mm. width also available.
Standard height is 2.028mm. Optionally, 2035mm. height is also available.
- » Standard faceplate has a 20x10mm. profile. Faceplates with a 20mmx7,5mm. profile can be ordered optionally in T2B3, TLB3, T2B5, TLB5 series locks.
- » It is also possible to include the EMB700 scratch-saver escutcheon rose.

Cylinder	mm.	Finish	Strike	3 points	5 points	5 frontal points
T60	60	AE	Short	TLB3566CE	TLB5566CE	
T60	70	AE	Short	TLB3567CE	TLB5567CE	
T60	60	AE	Long	TLB3566LE	TLB5566LE	TLBF566LE
T60	60	AC	Long	TLB3566LC	TLB5566LC	
T60	60	HN	Long	TLB3566LN		
T60	60	AI	Long	TLB3566LAI		TLBF567LE
T60	70	AE	Long	TLB3567LE	TLB5567LE	
S/C	--	AE	Short	TLB35SCCE	TLB55SCCE	
S/C	--	AC	Short	TLB35SCCC	TLB55SCCC	
S/C	--	HN	Short	TLB35SCCN	TLB55SCCN	
S/C	--	AI	Short	TLB35SCCAI	TLB55SCLC	
S/C	--	AE	Long	TLB35SCLC	TLB55SCLC	TLBF5SCLC
S/C	--	AC	Long	TLB35SCLC	TLB55SCLN	TLBF5SCLC
S/C	--	HN	Long	TLB35SCLN	TLBF5SCL	TLBF5SCLN
S/C	--	AI	Long	TLB35SCLAI	TLBF5SCLAI	

Underline: "Express 5" service.

No underline: 15 working days maximum.

Maximum lock length

Door length	T2B3, TLB3 and TLBF	T2B5 and TLB5
Standard	2030mm	2030mm
Minimum	1850mm	1875mm
Max. without accessories	2300	2300
Max. with accessories	SPTL28 (28mm)	SPTL10 (10 mm)





TLB3

TLBF

TLB5

"U" profile forend



Escutcheon E700L included