

Mortise electromagnetic locks



ASSA ABLOY

These locks are embedded in the door avoiding visual impact and offering several mounting options. They may be installed in any position; horizontally, vertically, bottom, top or side in sliding doors and swinging doors. The mortise electromagnetic locks

combine magnetic force with mechanical shear force. The shear force comes from two bolts which are located in the electromagnet and sit on the seats placed in the strike plate.

Standard range

Technical features

- » Aluminium housing
- » Operation temperature: -10°C to 55°C
- » Voltage: 12/24Vdc (Selectable)
Tolerance ±10



CEM750SS0F



CEM150SS0F



Product code	Holding force	Monitoring	Dimensions	Weight	Consumption
CEM750SS0F	600Kg	Hall	Lock: 180 x 30 x 27mm. Armature: 180 x 30 x 33mm.	1,2Kg	420mA(12Vcc)210mA(24Vcc)
CEM150SS0F	1000Kg	Hall	Lock: 251 x 30 x 34mm. Armature: 267 x 30 x 34mm.	1,8Kg	500mA(12Vcc)320mA(24Vcc)

High range

Technical features

- » Stainless Steel housing
- » Operation temperature: -40°C to +60°C
- » Voltage: 12/24Vdc (Auto)



Product code	Holding force	Monitoring	Dimensions	Weight	Consumption
SCGG030EN	300Kg		Lock: 181 x 29 x 24mm. Armature: 181 x 29 x 25mm.	1,2Kg	68mA(24Vcc)
SCGG045ES	600Kg	Hall	Lock: 268 x 38 x 30mm. Armature: 275 x 37 x 36mm.	2,8Kg	320mA(12Vcc)170mA(24Vcc)

Pour plus d'informations, visitez www.tesa.es
ou envoyer un e-mail à marketing@tesa.es