



Simple, tough and good value for money, the KL15 offers mechanical keyless access with Public or Private Function models suitable for a variety of locker and cabinet applications.

A durable, compact, easy to use mechanical lock. Designed to be both retrofitted or installed on new cabinets. Changing or resetting the code can be completed easily whilst the lock is still on the door, or if the code has been forgotten it can be retrieved using the master key.



Easy to install



Mechanical keyless access



Two years guarantee\*



Private and Public Functions

## FEATURES

- Code retrieval function
- Flush or surface mounted
- Anti-vandal handle
- Salt spray tested
- High / low temperature tested
- High / low humidity tested
- 4 wheel combination
- Up to 10,000 unique combinations
- Locked / unlocked indicators
- Public and Private Function
- Suitable for internal and external applications

# Anti-vandal Mechanical KL15



**ASSA ABLOY**

Experience a safer  
and more open world

## FUNCTIONS



### Private Function

The KL15 Private Function is ideal for use where the same, personal 4 digit code will be repeatedly used, e.g. an employee with the same locker/drawer in the workplace.



### Public Function

The KL15 Public Function is ideal for short term, multiple occupancy applications. The user enters a personal four digit code, this locks the lock. The same code is entered once only to open the lock, and is automatically zeroed. The lock remains open ready for the next user.



### Code Retrieval

Use the Master Key to retrieve the forgotten code by simply turning the dials individually until the correct code 'clicks' into place.



### Installation

The KL15 can be installed to fit either flush or surface mounted applications. All necessary fixings are supplied with the lock.



## PRODUCT DIMENSIONS



## TECHNICAL SPECIFICATIONS

FEATURE	DESCRIPTION
Functions	Public or Private Function
Code Length	4 digit
Code Storage	Single code
Suitable For	Internal and external applications*
Surface Mount	Fixed spindle suitable for panel thickness 0.8mm - 18mm (1/32" - 11/16")
Flush Fit	Suitable for panel thickness 0.8mm - 36mm (1/32" - 1 3/8")
Handing	Vertical, right hand and left hand
Indicators	Locked (red) / unlocked (green)
Fixings	All surface mount and flush fit fixings supplied as standard
Cam	Flat and cranked cam supplied as standard

Talleres de Escoriaza, S.A.U.  
OEM Division  
Sierra de Segura, 15  
28830 San Fernando de Henares  
Madrid - Spain  
Tel. 91 678 55 09  
Fax. 91 678 55 19  
email: [orders.oem@tesa.es](mailto:orders.oem@tesa.es)  
[www.tesa.es](http://www.tesa.es)



**ASSA ABLOY**

Experience a safer  
and more open world