


# ABLOY® LOCK OIL



**Product description**

The oil is available in two different pack sizes, 12x49 ml (8851049) bottles and 12x200 ml (8851200) bottles.

**LUBRICATION INSTRUCTIONS FOR END USER**

**Mechanical cylinders and lock cases**

For proper function and long life time, ABLOY mechanical locks need to be maintained regularly. One short spray of lock oil inside of the keyway once a year is enough to ensure proper and comfortable function of a lock in normal environmental conditions. In harsh conditions, it is recommended to observe if the lubrication is needed more often. To ensure proper lubrication, insert the key and rotate it clock- and counter-clockwise a few times after application of lubricant.

**Electromechanical cylinders**

**PROTEC² CLIQ® and ABLOY® PULSE**

To ensure proper function and long life time, ABLOY electromechanical cylinders require in normal conditions maintenance once a year, in harsh conditions maintenance is needed at least bi-annually. One short spray of lock oil to mechanical part in the back of keyway is enough to lubricate, electronics in the front of key way don't need lubrication. To ensure proper lubrication, use key to open lock a few times.

Please note that wrong lock oil or too much oil in electronics may cause issues in function of lock.

**Technical data**

Weight	(49 ml) (200 ml)
--------	---------------------

This content is protected by Intellectual Property Rights Laws. The title to the content shall not pass to you, and instead shall remain with Abloy Oy or a third party holding the title. Abloy develops continuously the products and solutions offered. Therefore, the information contained in the document is subject to change without notice. ABLOY PROVIDES THIS CONTENT ON AN "AS IS" BASIS WITHOUT ANY WARRANTIES OF ANY KIND, EXPRESS, IMPLIED, OR STATUTORY."